

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME****CB TEST CERTIFICATE**

Product

ICT/ITE Power Supply

Name and address of the applicant

GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647,  
UNITED STATES OF AMERICA

Name and address of the manufacturer

Same as applicant

Name and address of the factory

Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100-240VAC, 50-60Hz or 50/60Hz, Max. 0.5A  
Output: 3.3-48Vdc, Max. 2.6A, Max. 19.2W

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT\*21089-\*\*\*\*\*, GT\*21096-\*\*\*\*\*

Additional information (if necessary may also be reported on page 2)

Group differences for CENELEC countries and national differences for Japan, Australia / New Zealand, US and Canada are considered.

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

210602694SHA-001

This CB Test Certificate is issued by the National Certification Body

**Intertek Semko AB**  
**Torshamnsgatan 43**  
**Box 1103**  
**SE-164 22 Kista, Sweden****intertek**

Signature:

Date: 11 November, 2021

Hyden Li



**Factories**

GlobTek (Suzhou) Co., Ltd  
Building 4, No. 76 JinLing East Road, Suzhou  
Industrial Park, Suzhou, JiangSu, 215021,  
CHINA

GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647  
USA

**Additional information**

Explanation of models GT\*21089-\*\*\*\*\* and GT\*21096-\*\*\*\*\*

**GT\*21089-\*\*\*\*\***

The 1st “\*” part can be ‘M’ or ‘-’ or ‘H’ for market identification and not related to safety.

The 2nd “\*” denotes the rated output wattage designation, which can be “01” to “19”, in step of 1 denote 1W.

The 3rd “\*” denotes the standard rated output voltage designation, which can be “03”, “05”, “06”, “09”, “12”, “15”, “18”, “24”, “48”;

The 4th “\*” is optional deviation, subtracted from standard output voltage, which can be “-0.01” to “-23.99” with interval of 0.01, or blank to indicate no voltage different.

The 5th “\*” =T2 means desktop class II with C8 AC inlet

=T3 means desktop class I or class II with functional earth with C14 AC inlet

=T3A means desktop class I or class II with functional earth with C6 AC inlet

The last “\*” denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

**GT\*21096-\*\*\*\*\***

The 1st “\*” part can be ‘M’ or ‘-’ or ‘H’ for market identification and not related to safety.

The 2nd “\*” denotes the rated output wattage designation, which can be “01” to “19”, in step of 1 denote 1W.

The 3rd “\*” denotes the standard rated output voltage designation, which can be “03”, “05”, “06”, “09”, “12”, “15”, “18”, “24”, “48”;

The 4th “\*” is optional deviation, subtracted from standard output voltage, which can be “-0.01” to “-23.99” with interval of 0.01, or blank to indicate no voltage different.

The 5th “\*” =F means Open Frame class I or class II with functional earth

=FW means Open Frame class II

=R means PCB mounted class I or class II with functional earth

=RW means PCB mounted class II

The last “\*” denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

Date: 11 November, 2021

Signature:

