

C-Tick Test Report

Issued Date : Sep. 04, 2008
Project No. : 0809C022A
Equipment : ITE POWER SUPPLY
Model Name : GT-21131-7224

Applicant : GlobTek, Inc.
Address : 186 Veterans Dr. Northvale N.J 07647
USA
Manufacture : GlobTek, Inc.
Address : 186 Veterans Dr. Northvale N.J 07647
USA

Tested by:
Neutron Engineering Inc. EMC Laboratory
Date of Test:
Sep. 02, 2008 ~ Sep. 03, 2008

Testing Engineer: _____
Josh Lin
(Josh Lin)

Technical Manager: _____
Jeff Yang
(Jeff Yang)

Authorized Signatory: _____
James Chiu
(James Chiu)

NEUTRON ENGINEERING INC.

B1, No.37, Lane 365, Yang Guang St., NeiHu
District 114., Taipei, Taiwan
TEL : (02) 2657-3299 FAX : (02) 2657-3331



Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (NML) of R.O.C., or National Institute of Standards and Technology (NIST) of U.S.A.

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron's** authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
1 . CERTIFICATION	4
2 . SUMMARY OF TEST RESULTS	5
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY	6
3 . GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	8
3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
3.4 DESCRIPTION OF SUPPORT UNITS	10
4 . EMC EMISSION TEST	11
4.1 CONDUCTED EMISSION MEASUREMENT	11
4.1.1 POWER LINE CONDUCTED EMISSION	11
4.1.2 MEASUREMENT INSTRUMENTS LIST	11
4.1.3 TEST PROCEDURE	12
4.1.4 DEVIATION FROM TEST STANDARD	12
4.1.5 TEST SETUP	12
4.1.6 BLOCK DIAGRAM OF TEST SETUP	13
4.1.7 EUT OPERATING CONDITIONS	13
4.1.8 TEST RESULTS	14
4.2 RADIATED EMISSION MEASUREMENT	16
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	16
4.2.2 MEASUREMENT INSTRUMENTS LIST	17
4.2.3 TEST PROCEDURE	17
4.2.4 DEVIATION FROM TEST STANDARD	17
4.2.5 TEST SETUP	18
4.2.6 BLOCK DIAGRAM OF TEST SETUP	18
4.2.7 EUT OPERATING CONDITIONS	18
4.2.8 TEST RESULTS	19

1. CERTIFICATION

Equipment: ITE POWER SUPPLY

Brand Name: GlobTek

Model Name: GT-21131-7224

Applicant: GlobTek, Inc.

Factory: Sunny Computer Technology Co., Ltd.

Address: HengLi New Town Zone, Dong Guan City, GuangDong 523477, P. R. China

Date of Test: Sep. 02, 2008 ~ Sep. 03, 2008

Standards: AS/NZS CISPR 22:2006 Class B./ CISPR 22:2005+A1: 2005+A2: 2006

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-SMA-1-0809C022A) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

EMC Emission				
Standard	Test Item	Limit	Judgment	Remark
AS/NZS CISPR 22:2006	Conducted Emission	Class B	PASS	
	Radiated Emission	Class B	PASS	

NOTE:

(1) " N/A" denotes test is not applicable in this Test Report.

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **C01/OS02** at the location of No.132-1, Lane 329, Sec. 2, Palain Road, Shijr City, Taipei, Taiwan.

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95%**.

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	NOTE
C01	ANSI	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)	NOTE
OS-01	ANSI	30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	
OS-02	ANSI	30MHz ~ 200MHz	V	2.48	
		30MHz ~ 200MHz	H	2.16	
		200MHz ~ 1,000MHz	V	2.50	
		200MHz ~ 1,000MHz	H	2.66	

3. GENERAL INFORMATION**3.1 GENERAL DESCRIPTION OF EUT**

Equipment	ITE POWER SUPPLY
Brand Name	GlobTek
Model Name	GT-21131-7224
OEM Brand/ Model	N/A
Model Difference	Compared with previous report (NEI-SMA-1-0809C022), the differences are applicant, model name and brand.
Product Description	The EUT is a ITE POWER SUPPLY. Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.
Power Source	AC Mains.
Power Rating	AC I/P 100-240V 50-60Hz 1.6A MAX DC O/P +24V, 3.0A
Connecting I/O Port(s)	Please refer to the User's Manual
Products Covered	N/A
EUT Modification(s)	N/A

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.


3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	FULL LOAD
Mode 2	HALF LOAD

For Conducted / Radiated Test	
Final Test Mode	Description
Mode 1	FULL LOAD

3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



C-1 Power Cable

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	ITE POWER SUPPLY	GlobTek	GT-21131-7224	DOC	N/A	EUT
E-2	Dummy Load	N/A	N/A	N/A	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	YES	1.9M	

- Note:
- (1) The support equipment was authorized by Declaration of Conformity.
 - (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION (FREQUENCY RANGE 150KHZ-30MHZ)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

4.1.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Test Cable	N/A	C01	N/A	Oct. 10, 2008
2	Pulse Limiter	Electro-Metrics	EM-7600	112644	Nov. 27, 2008
3	EMI Test Receiver	R&S	ESCI	100080	Mar. 10, 2009
4	LISN	Rolf Heine	NNB-2/16Z	98053	Dec. 30, 2008

Remark: " N/A" denotes No Model Name, Serial No. or No Calibration specified.


4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.


4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



4.1.6 BLOCK DIAGRAM OF TEST SETUP



4.1.7 EUT OPERATING CONDITIONS

The EUT exercise program used during radiated and/or conducted emission measurement was designed to exercise the various system components in a manner similar to a typical use.


4.1.8 TEST RESULTS

E.U.T :	ITE POWER SUPPLY	Model Name :	GT-21131-7224
Temperature :	28 °C	Relative Humidity :	50 %
Pressure :	1010 hPa	Test Voltage :	AC 240V/50Hz
Test Mode :	FULL LOAD		

Freq. (MHz)	Terminal L/N	Measured(dBuV)		Limits(dBuV)		Margin (dB)	Note
		QP-Mode	AV-Mode	QP-Mode	AV-Mode		
0.16	Line	55.34	41.59	65.73	55.73	-10.39	(QP)
0.21	Line	47.80	*	63.21	53.21	-15.41	(QP)
0.78	Line	37.06	*	56.00	46.00	-18.94	(QP)
3.33	Line	42.20	*	56.00	46.00	-13.80	(QP)
7.48	Line	56.02	40.62	60.00	50.00	-3.98	(QP)
9.14	Line	49.89	41.56	60.00	50.00	-8.44	(AV)

Remark

- (1) Reading in which marked as QP means measurements by using are Quasi-Peak Mode with Detector BW=9KHz; SPA setting in RBW=10KHz,VBW =10KHz, Swp. Time = 0.3 sec./MHz. Reading in which marked as AV means measurements by using are Average Mode with instrument setting in RBW=1MHz,VBW=10Hz, Swp. Time =0.3 sec./MHz.
- (2) All readings are QP Mode value unless otherwise stated AVG in column of Note. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a "*" marked in AVG Mode column of Interference Voltage Measured.
- (3) Measuring frequency range from 150KHz to 30MHz.




E.U.T :	ITE POWER SUPPLY	Model Name :	GT-21131-7224
Temperature :	28 °C	Relative Humidity :	50 %
Pressure :	1010 hPa	Test Voltage :	AC 240V/50Hz
Test Mode :	FULL LOAD		

Freq. (MHz)	Terminal L/N	Measured(dBuV)		Limits(dBuV)		Margin (dB)	Note
		QP-Mode	AV-Mode	QP-Mode	AV-Mode		
0.16	Neutral	54.17	40.33	65.73	55.73	-11.56	(QP)
0.21	Neutral	46.15	*	63.21	53.21	-17.06	(QP)
0.26	Neutral	41.26	*	61.43	51.43	-20.17	(QP)
5.00	Neutral	44.11	32.07	56.00	46.00	-11.89	(QP)
8.26	Neutral	53.66	35.41	60.00	50.00	-6.34	(QP)
13.55	Neutral	44.35	*	60.00	50.00	-15.65	(QP)

Remark

- (1) Reading in which marked as QP means measurements by using are Quasi-Peak Mode with Detector BW=9KHz; SPA setting in RBW=10KHz,VBW =10KHz, Swp. Time = 0.3 sec./MHz. Reading in which marked as AV means measurements by using are Average Mode with instrument setting in RBW=1MHz,VBW=10Hz, Swp. Time =0.3 sec./MHz.
- (2) All readings are QP Mode value unless otherwise stated AVG in column of Note. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a " * " marked in AVG Mode column of Interference Voltage Measured.
- (3) Measuring frequency range from 150KHz to 30MHz.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 10m)
	dBuV/m	dBuV/m
30 – 230	40	30
230 – 1000	47	37

Notes:

- (1) The limit for radiated test was performed according to as following: CISPR 22/ FCC PART 15B /ICES-003.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RADIATED EMISSION MEASUREMENT (ABOVE 1000MHZ)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
1000-3000	76	50	70	50
3000-6000	80	60	74	54

Notes:

- (1) The lower limit applies at the transition frequency.

FREQUENCY RANGE OF RADIATED MEASUREMENT (FOR UNINTENTIONAL RADIATORS)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 6 GHz, whichever is lower

4.2.2 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Log-Bicon Antenna	Schwarzbeck	VULB 9160	3173	Jul. 01, 2009
2	Test Cable	N/A	10M_OS02	N/A	Oct. 10, 2008
3	Test Cable	N/A	OS02	N/A	Oct. 10, 2008
4	Pre-Amplifier	Anritsu	MH648A(OS02)	M10061	Oct. 10, 2008
5	EMI Test Receiver	R&S	ESCI	100082	Feb. 23, 2009
6	Antenna Mast	Chance Most	CMTB-1.5	N/A	N/A
7	Turn Table	Chance Most	CMTB-1.5	N/A	N/A

Remark: " N/A" denotes No Model Name / Serial No. and No Calibration specified.


4.2.3 TEST PROCEDURE

- a. The measuring distance of at 10 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m or 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting radiated emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



4.2.6 BLOCK DIAGRAM OF TEST SETUP



4.2.7 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.7 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.8 TEST RESULTS

E.U.T :	ITE POWER SUPPLY	Model Name :	GT-21131-7224
Temperature :	29 °C	Relative Humidity :	60%
Pressure :	1003 hPa	Test Voltage :	AC 240V/50Hz
Test Mode :	FULL LOAD		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
42.51	V	37.28	-10.73	26.55	30.00	- 3.45	
108.59	V	31.50	-10.96	20.54	30.00	- 9.46	
205.45	V	31.64	-12.09	19.55	30.00	- 10.45	
245.86	V	32.71	-10.25	22.46	37.00	- 14.54	
299.93	V	31.92	-8.06	23.86	37.00	- 13.14	
357.86	V	29.67	-6.59	23.08	37.00	- 13.92	

Remark :

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz ◦
- (2) All readings are Peak unless otherwise stated QP in column of 『Note 』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz ◦
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table ◦



E.U.T :	ITE POWER SUPPLY	Model Name :	GT-21131-7224
Temperature :	29 °C	Relative Humidity :	60%
Pressure :	1003 hPa	Test Voltage :	AC 240V/50Hz
Test Mode :	FULL LOAD		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
38.55	H	30.85	-10.40	20.45	30.00	- 9.55	
124.51	H	31.51	-9.86	21.65	30.00	- 8.35	
150.55	H	33.33	-9.52	23.81	30.00	- 6.19	
200.63	H	35.66	-11.82	23.84	30.00	- 6.16	
263.62	H	32.21	-9.32	22.89	37.00	- 14.11	
294.52	H	30.26	-8.09	22.17	37.00	- 14.83	

Remark :

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz ◦
- (2) All readings are Peak unless otherwise stated QP in column of 『Note 』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform ◦
- (3) Measuring frequency range from 30MHz to 1000MHz ◦
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table ◦

