

CB TEST CERTIFICATE CERTIFICAT D'ESSAI OC

Product
Produit

Power supply for business machine

Name and address of the applicant
Nom et adresse du demandeurGlobTek, Inc.
186 Veterans Drive
Northvale, NJ 07647
USAName and address of the manufacturer
Nom et adresse du fabricantGlobTek, Inc.
186 Veterans Drive
Northvale, NJ 07647
USAName and address of the factory
Nom et adresse de l'usineNote: When more than one factory, please report on page 2
Note: Lorsque il y a plus d'une usine, veuillez utiliser la deuxième page☒ Additional information on page 2Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

Input: 0.5A 100-240Vac 50-60Hz, Cl. I or Cl. II

Trademark (if any)
Marque de fabrique (si elle existe)Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeurModel / Type Ref.
Ref. De type

GT-41082-WWVV-X.X-AB

Additional information (if necessary may also be
reported on page 2)☒ Additional information on page 2Les informations complémentaires (si nécessaire,
peuvent être indiqués sur la deuxième pageA sample of the product was tested and found
to be in conformity withUn échantillon de ce produit a été essayé et a été
considéré conforme à laAs shown in the Test Report Ref. No. which forms part
of this Certificate

312254

Comme indiqué dans le Rapport d'essais numéro de
référence qui constitue partie de ce CertificatThis CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**Gaustadalléen 30
NO-0373 Oslo, Norway

Date: 28-07-2016

Signature: Juan Z. Kleppenes
Certification Department

GlobTek, Inc.
186 Veterans Drive
Northvale, NJ 07647
USA

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial
Park, Suzhou, JiangSu 215021
China

Additional information(if necessary)

Information complémentaire (si nécessaire)

Output: 5-15Vdc, max 18W. In model name, "WW" is the rated output wattage designation, with a maximum value of "18". "VV" is the standard rated output voltage designation, with a maximum value of "15". "-X.X" is optional or blank and denotes the output voltage differentiator, subtracting or adding X.X volts from standard output voltage VV in 0.1V increments. "VV-X.X" together denotes a voltage range of "5-15" Vdc. A=T. B= 2 or 3 or 3A, "2" means class II, 3 or 3A means Class I, where "3" presents C14 type inlet, "3A" presents C6 type inlet.



Gaustadalléen 30
NO-0373 Oslo, Norway

Date: 28-07-2016

A handwritten signature in blue ink, reading "Juan Z. Kleppenes".

Signature: Juan Z. Kleppenes
Certification Department