

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ICT/ITE power supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Dr Northvale, NJ07647, USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100-240Vac, 50-60Hz, 1.0A.
Output: 12 Vdc, 3 A max or 12.1-15 Vdc or 3 A max or 15.1-19 Vdc, 2.66 A max or 19.1-24 Vdc, 2.1 A max. Class II

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*46401-****, GT*46401-***-W2Z*

Additional information (if necessary may also be reported on page 2)

See page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

200300053TWN-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Torshamnsgatan 43
Box 1103
SE-164 22 Kista, Sweden

intertek

Signature:

Ted Wu

Date: 15 April, 2020

Factories

1. GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647, USA
2. GlobTek (Suzhou) Co., Ltd.
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou, JiangSu 215021, China

Additional information (if necessary)

The national differences for AU and US have been checked.
The product has also been checked according to EN 62368-1:2014+A11

Explanation of model designation GT*46401-****, GT*46401-***-W2Z* :

The 1st symbol "*" can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2rd symbol "*" denotes the rated output wattage designation, with a maximum value of "40".

The 3th symbol "*" denotes the standard rated output voltage designation, which can be "12", "15", "19", "24".

The 4th symbol "*" is optional deviation, subtracted from standard output voltage, which can be "-0.1" to "-4.9" with interval of 0.1, or blank to indicate no voltage different.

The last symbol "*" can be any six character means "0-9", "A-Z", "()", "[]", "-" or blank for marketing purposes.

(-W2Z can be optional, when it is blank, denote to be with replaceable plug)

Z designates type of plug for market identification or can be blank.

(E for European plug, U for British plug, blank for North American / Japan plug/Taiwan plug, C for Chinese plug, I for India plug, A for Australia plug, K for Korea plug, AR for Argentina plug, BR for Brazilian plug, SA or AF for South African plug.)

Date: 15 April, 2020

Signature:

