

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20151013-E170507  
**Report Reference** E170507-20130930  
**Issue Date** 2015-OCTOBER-13

**Issued to:** GLOBTEK INC  
186 VETERANS DR  
NORTHVALE , NJ 07647  
United States

**This is to certify that  
representative samples of**

POWER SUPPLIES, INFORMATION TECHNOLOGY  
EQUIPMENT INCLUDING ELECTRICAL BUSINESS  
EQUIPMENT

For models refer to Addendum Page

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 60950-1 and CAN/CSA C22.2 No. 60950-1-07 -  
(Information Technology Equipment - Safety - Part 1:  
General Requirements)

**Additional Information:** See the UL Online Certifications Directory at  
[www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's  
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please  
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20151013-E170507  
**Report Reference** E170507-20130930  
**Issue Date** 2015-OCTOBER-13

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Switching Adapter - GT-81088-WWVV-X.X-W2 series: WW is the standard rated output wattage, with a maximum "6"  
VV is the standard rated output voltage designation, with a maximum value of "12"; -X.X is optional or blank and denotes the output voltage differentiator, subtracting or adding X.X volts from standard output voltage VV in 0.1V increments, blank is to indicate the no voltage different. VV-X.X together denotes the voltage range from 5.0 to 7.5Vdc and 8.0 to 12.0Vdc

GT-81087-WWVV-X.X-W2 series: WW is the standard rated output wattage, with a maximum "20.4"; VV is the standard rated output voltage designation, with a maximum value of "18"; -X.X is optional or blank and denotes the output voltage differentiator, subtracting or adding X.X volts from standard output voltage VV in 0.1V increments, blank is to indicate the no voltage different. VV-X.X together denotes the voltage range from 5 to 7.5Vdc and 9 to 12Vdc and 15 to 18Vdc.

GT-81090-06VV-X.X-W2-USB series and GT-81090-06VV-X.X-WR2-USB series: VV is the standard rated output voltage designation, with a maximum value of "7.5"; -X.X is optional or blank and denotes the output voltage differentiator, subtracting or adding X.X volts from standard output voltage VV in 0.1V increments, blank is to indicate the no voltage different; VV-X.X together denotes the voltage range from 5.0 to 7.5Vdc.

GT-81091-WWVV-X.X-TZ series: WW is the standard rated output wattage, with a maximum "60"; VV is the standard rated output voltage designation, with a maximum value of "24"; -X.X is optional or blank and denotes the output voltage differentiator, subtracting or adding X.X volts from standard output voltage VV in 0.1V increments, blank is to indicate the no voltage different; "Z" presents different inlets, where "3" presents C14, "3A" presents C6; VV-X.X together denotes the voltage range from 1 to 12Vdc and 19 to 24Vdc

GT-81091-WWVV-X.X-T2 series: WW is the standard rated output wattage, with a maximum "60"; VV is the standard rated output voltage designation, with a maximum value of "24"; -X.X is optional or blank and denotes the output voltage differentiator, subtracting or adding X.X volts from standard output voltage VV in 0.1V increments, blank is to indicate the no voltage different; VV-X.X together denotes the voltage range from 1-12Vdc and 19 to 24Vdc.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20151013-E170507  
**Report Reference** E170507-20130930  
**Issue Date** 2015-OCTOBER-13

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

GT-81085-WWVV-X.X-W2 series: WW is the standard rated output wattage, with a maximum "15" ; VV is the standard rated output voltage designation, VV can be 07.5,13.5,16.6,24; -X.X is optional or blank and denotes the output voltage differentiator, subtracting or adding X.X volts from standard output voltage VV in 0.1V increments, blank is to indicate the no voltage different.

ITE POWER SUPPLY - GT-83080-WW05-USB-W2: WW is the standard output wattage, with a maximum value of "05"

GT-83084-WWVV-X.X-USB-W2 - WW is the standard output wattage, with a maximum value of "11" VV is the standard rated output voltage designation, with a value of "06"; -X.X denote the output voltage differentiator, subtracting X.X volts from standard output voltage VV in 0.1V increments, the actual output voltage rang is 5V-5.2V, blank is to indicate the no voltage different.

ITE POWER SUPPLY - GT-83083-WW05-USB-W2 (fix plug), GT-83083-WW05-USB (replaceable plug); WW is the standard output wattage, with a maximum value of "05".

GT-83081-WWVV-X.X-W2, WW is the standard output wattage, with a maximum value of "12"; VV is the standard rated output voltage designation, with a maximum value of "15"; -X.X is optional or blank and denotes the output voltage differentiator, subtracting or adding X.X volts from standard output voltage VV in 0.1V increments, blank is to indicate the no voltage different.

GT-83082-WW12-W2, WW is the standard output wattage, with a maximum value of "36"



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

