




Ref. Certif. No.

SE-93534

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	ITE Power supply
Name and address of the applicant	GLOBTEK INC 186 VETERANS DRIVE, NORTHVALE NJ 07647, USA
Name and address of the manufacturer	Same as applicant
Name and address of the factory <i>Note: When more than one factory, please report on page 2</i>	See page 2
Ratings and principal characteristics	See page 2
Trademark (if any)	
Customer's Testing Facility (CTF) Stage used	-
Model / Type Ref.	GT*41061-***
Additional information (if necessary may also be reported on page 2)	See page 2
A sample of the product was tested and found to be in conformity with	IEC 60950-1:2005+A1+A2
As shown in the Test Report Ref. No. which forms part of this Certificate	171200473SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 13 March 2019

intertek

Signature:

Robin Xu

Factories

GLOBTEK INC
186 VETERANS DRIVE,
NORTHVALE NJ 07647, USA

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76 JinLing East Road
Suzhou Industrial Park
Suzhou JiangSu, 215021, CHINA

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 0.6A

Output: The model designations and ratings are detailed as follows:

Model	Rated output voltage range	Max. rated output current	Max. rated output power	Transformer designation
GT*41061-*12*	5-12Vdc	3.6A	18W	TF001
GT*41061-*18*	12.1-18Vdc	1.49A	18W	TF002
GT*41061-*24*	18.1-24Vdc	1.0A	18W	TF003
GT*41061-*30*	24.1-30Vdc	0.75A	18W	TF004

Additional information (if necessary)

Explanation of model designation GT*41061-***:

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" part denotes the rated output wattage designation, which can be "01" to "18", with interval of 1.

The 3rd "*" part denotes the standard rated output voltage designation, which can be "12", "18", "24" or "30".

These standard rated output voltage designations correspond to four isolated transformer models. Each transformer model is identical in insulation construction including clearance and creepage except number of turns per coil.

The 4th "*" part is optional, which can be "-0.1" to "-7.0" with interval of 0.1 to denote voltage deviation or blank to indicate no voltage different.

The result by subtracting the deviation value from the standard rated output voltage denotes the rated output voltage, with a range of 5 - 30 volts.

Test performed on 5Vdc/3A output adapter model and 30Vdc/0.6A output adapter model as worst condition, and also performed on other output models for reference.

Group and national differences for the CENELEC countries, and national differences for Canada, China, Korea, Japan, USA, Australia and New Zealand have been checked.

Date: 13 March 2019

Signature:

