






VERIFICATION STATEMENT	
EN 60950-1:2006+A11:2009+A1:2010+A12:2011+ A2:2013	
Information technology equipment – Safety – Part 1: General requirements	
Report Reference No.	: 161200824SHA-001 (Based on CB certif. no. SE-86407)
Tested by (+ signature)	: Albert Zhou 
Approved by (+ signature)	: Will Wang 
Date of issue	: 2017-03-29
Contents	: 4 pages
Testing laboratory Name	: Intertek Testing Services Shanghai
Address	: Building 86, 1198 Qinzhou Road (North), 200233 Shanghai, China
Testing location	: Same as above
Client Name	: GlobTek, Inc.
Address	: 186 Veterans Dr. Northvale, NJ 07647 USA
Standard	: EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013
Test procedure	: S mark
Non-standard test method	: N.A.
Test item Description	: ITE Power Supply
Trademark	: 
Model and/or type reference	: GT*961200P****, GT*96900P**** and GT*41133-**** Refer to page 2 for details.
Rating(s)	: Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-54VDC, Max. 10A, Max 120W Output: Refer to page 3 for details.
Manufacture	: GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647 USA
Factory	: GlobTek (Suzhou) Co., Ltd Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China
Remarks for acceptance and review work conducted by above qualified testing laboratory	
Sample Number reviewed	: 18 pcs

Remark	: The product and the mentioned test reports comply with Swedish standard and national deviations, if any. The sample as shown in following page(s) is still corresponding with the one mentioned in CB test report. We concluded this statement verifies that above standards are fulfilled.
Test item description	: No tests are needed for this product.
Statement for deviations, if any.....	: National difference for Sweden has been evaluated in CB report.

Model similarity:**GT*961200P****, GT*96900P**** and GT*41133-*******

The 1st “*” part can be ‘M’ or ‘-’ or ‘H’ for market identification and not related to safety.

When model = GT*41133-*****

The 2nd “*” denotes the rated output wattage designation, which can be “01” to “90”, with interval of 1.

The 3rd “*” denotes the standard rated output voltage designation, which can be “16”, “24”, “35” and “48”.

The 4th “*” part is optional, which can be “-0.1” to “-12.9” with interval of 0.1 to denote voltage deviation or blank to indicate no voltage different.

The 3rd “*” and 4th “*” together denote the output voltage, with a range of 12 - 48 volts

The 5th “*”

=-T2 means desktop class II with C8 AC inlet

=-T3A means desktop class I with C6 AC inlet

=-F means Open Frame class I

=-FW means Open Frame class II

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

When model = GT*961200P** and GT*96900P******

The 2nd “*” denotes the rated output wattage designation, which can be “-01” to “-120”, with interval of 1 and “-” can be omitted.

The 3rd “*” denote the standard rated output voltage designation, which can be “12” to “54” or “12.0” to “54.0” in 0.1V increments

The 4th “*”

=-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I with C14 AC inlet

=-T3TAB means desktop class I with C14 AC inlet and housing with a tab.

=-T3A means desktop class I with C6 AC inlet

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes

Ratings:

When model = GT*41133-*****, Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-48Vdc, Max. 7.5A, Max. 90W

When model = GT*96900P****, Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-54Vdc, Max. 7.5A, Max. 90W

When model = GT*961200P****, Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-54Vdc, Max. 10A, Max. 120W

Model list:

GT*41133-** Desktop models and open frame models**

Model	Output Voltage	Max. output current	Max. output power
GTM41133-*16*-T2/T3A/F/FW*	12-16Vdc	7.5A	90W
GTM41133-*24*-T2/T3A/F/FW*	16.1-24Vdc	5.6A	90W
GTM41133-*35*-T2/T3A/F/FW*	24.1-35Vdc	3.73A	90W
GTM41133-*48*-T2/T3A/F/FW*	35.1-48Vdc	2.56A	90W

GT*961200P** and GT*96900P**** Desktop models**

Model	Output Voltage	Max. output current	Max. output power
GT*96900P**- T2/T2A/T3/T3A/T3TAB*	12-54Vdc	7.5A	90W
GT*961200P**- T2/T2A/T3/T3A/T3TAB*	12-54Vdc	10A	120W

Specification and key information involved in original CB certificate and test report

Involved Ref. Certif. no.....	: SE-86407
Issued date.....	: 2017-03-24
Original. Certif. no	: SE-86407
Issued date.....	: 2017-03-24
Test item description.....	: ITE Power Supply
Applicant's Name	: GlobTek, Inc.
Address	: 186 Veterans Dr. Northvale, NJ 07647 USA
Manufacturer.....	: GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647 USA
Factory	: GlobTek (Suzhou) Co., Ltd Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou, JiangSu 215021, China
Technical data.....	: Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-54VDC, Max. 10A, Max 120W Output: Refer to page 3 for details.
Referred standard	: IEC 60950-1:2005 + A1:2009 + A2:2013 and EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013 and National difference for CENELEC countries, Singapore, Japan, China, Australia/New Zealand, Korea, Canada and USA
Model and/or type reference	: GT*961200P****, GT*96900P**** and GT*41133-**** Refer to page 2 for details.
Involved test report	: 161200822SHA-001