



Ref. Certif. No.

**SE-88962**

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR  
ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

**CB TEST CERTIFICATE**

Product

Power supply (Limited use for House Hold products only)

Name and address of the applicant

GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647 USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


*Note: When more than one factory, please report on page 2*

See page 2

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 1.0A;  
Output: 5-36VDC, Max. 6A, Max. 40W

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT\*46402-\*\*\*

Additional information (if necessary may also be  
reported on page 2)

See page 2

A sample of the product was tested and found  
to be in conformity with

IEC 60335-1:2010+A1+A2

As shown in the Test Report Ref. No. which forms part  
of this Certificate

170800263SHA-001

This CB Test Certificate is issued by the National Certification Body

**Intertek Semko AB**  
Box 1103  
SE-164 22 Kista, Sweden  
Int +46 8 750 00 00

Date: 16 November 2017

**Intertek**

Signature:

Robin Xu

**Factories**

1. GlobTek, Inc.

186 Veterans Dr. Northvale, NJ 07647 USA

2. GlobTek (Suzhou) Co., Ltd

Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

**Additional information (if necessary)**

Explanation of model GT\*46402-\*\*\*:

The 1<sup>st</sup> symbol "\*" part can be 'M' or '-' or 'H' for market identification and not related to safety.The 2<sup>nd</sup> symbol "46" denotes the rated output wattage designation, which can be "01" to "40", with interval of 1.The 3<sup>rd</sup> symbol "02" denotes the standard rated output voltage designation, which can be "05" to "36" or "5.0" to "36.0", with interval of 0.1.

The last symbol "\*\*\*" denote any six character = 0-9 or A-Z or ( ) [ ] or - or blank for marketing purposes

**Model List:**

Model	Input	Output voltage (Vdc)	Output current (A)	Max. output power (W)
GT*46402-***	100-240V~, 50-60Hz, 1.0A	5.0-8.9Vdc	6A	40W
		9.0-14.9Vdc	4.44A	40W
		15.0-24.0Vdc	2.66A	40W
		24.1-36.0Vdc	1.66A	40W

Group differences for CENELEC countries and national differences for Germany, United Kingdom, Australia and United States are considered.

Date: 16 November 2017

Signature:

