



Ref. Certif. No.

SE-86908

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR
ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ITE Power Supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100-240VAC, 50-60Hz, 1.5A
Output: 12-54VDC, Max. 9.2A, Max. 120W

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*961200P****, GT*96900P****

Additional information (if necessary may also be
reported on page 2)

See page 2

A sample of the product was tested and found
to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part
of this Certificate

161200822SHA-003

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 8 May 2017

Intertek

Signature:

Gary Hu



Ref. Certif. No.

SE-86908

Factories

1, GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 USA

2, GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park,
Suzhou, JiangSu, 215021, China

Additional information (if necessary)

Model similarity:

GT*961200P****, GT*96900P****

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" denotes the rated output wattage designation, which can be "-01" to "-120", with interval of 1 and "-" can be omitted.

The 3rd "*" denote the standard rated output voltage designation, which can be "12" to "54" or "12.0" to "54.0" in 0.1V increments

The 4th "*" =-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I with C14 AC inlet

=-T3TAB means desktop class I with C14 AC inlet and housing with a tab.

=-T3A means desktop class I with C6 AC inlet

The last * denote any six character = 0-9 or A-Z or [] or - or blank for marketing purposes

Ratings:

When model = GT*96900P****, Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-54Vdc, Max. 7.5A, Max. 90W

When model = GT*961200P****, Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-54Vdc, Max. 9.2A, Max. 120W

Date: 8 May 2017

Signature: 