



Ref. Certif. No.

SG ITS-28720

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME**

CB TEST CERTIFICATE

Product

ICT/ITE Power Supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647, United States of America

Name and address of the manufacturer

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647, United States of America

Name and address of the factory

Note: When more than one factory, please report on page 2

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou,
JiangSu, 215021, China

☒ [Additional Information on page 2](#)

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz or 50/60Hz, 2.2A, Class I or Class II
Output: 12-54VDC, Max.13.33A, Max. 180W

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

See page 2

Additional information (if necessary may also be reported on page 2)

Group and National differences for CENELEC countries (EN 62368-1:2014 + A11:2017) and national differences of United States of America and Canada, JAPAN, Australia and New Zealand and National Requirements of SINGAPORE were checked.

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

220309107SZN-001

This CB Test Certificate is issued by the National Certification Body

Intertek Testing Services (Singapore) Pte Ltd
5, Pereira Road, #06-01
Asiawide Industrial Building
Singapore 368025

intertek

Date: 07 June 2022

Signature:

Ong Keng Chuan



Ref. Certif. No.

SG ITS-28720

Name and address of the factory

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647, United States of America

Model / Type Ref.

GT*961600P****, GT*961800P****

(The 1st "*" part can be 'M' or 'L' or 'H' for market identification and not related to safety.

The 2nd "*" can be "01" to "180", denotes the rated output wattage designation from 1W to 180W, with interval of 1W.

The 3rd "*" can be "12" to "54" or "12.0" to "54.0", denote the standard rated output voltage designation from 12VDC to 54VDC, with interval of 0.1V.

The 4th "*" = -T2 means desktop Class II with C8 AC inlet

= -T2A means desktop Class II with C18 AC inlet

= -T3 means desktop Class I with C14 AC inlet

= -T3A means desktop Class I with C6 AC inlet

= -TW means desktop with input wires without plug (Certificated plugs will be fitted before use by skilled person)

= -TP means desktop with power cord and US Plug

The last * denote any six character can be 0-9 or A-Z or () [] or – or blank for marketing purposes.)

Date: 07 June 2022

Signature:


Ong Keng Chuan