



Ref. Certif. No.

SE-91903

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR
ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ITE Power Supply

Name and address of the applicant

GLOBTEK INC
186 VETERANS DRIVE, NORTHVALE NJ 07647
USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory

Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 2.2A;
Output: 12-54VDC, Max. 13.33A, Max. 180W
See model list for detail

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*961600P****, GT*961800P****

Additional information (if necessary may also be
reported on page 2)

See page 2

A sample of the product was tested and found
to be in conformity with

IEC 60950-1:2005+A1+A2

As shown in the Test Report Ref. No. which forms part
of this Certificate

180401370SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 17 September 2018

intertek

Signature:

Gary Hu

Factories

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 USA

GlobTek (Suzhou) Co., Ltd.
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

Additional information (if necessary)

Explanation of type designation

GT*961600P****, GT*961800P****

(The 1st symbol "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd symbol "*" can be "01" to "180", denotes the rated output wattage designation from 1W to 180W, with interval of 1W.

The 3rd symbol "*" can be "12" to "54" or "12.0" to "54.0", denote the standard rated output voltage designation from 12V to 54V, with interval of 0.1V.

The 4th symbol "*" =-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I with C14 AC inlet

=-T3A means desktop class I with C6 AC inlet

=-TW means desktop with input wires without plug

=-TP means desktop with power cord and US plug

The last symbol "*" denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.)

Model List:

| Model | Input | Output voltage (Vdc) | Max. output current (A) | Max. output power (W) |
|----------------------------------|--------------------------------|----------------------|-------------------------|-----------------------|
| GT*961600P**** GT*961800P**** | 100-240V~, 50-60Hz, 2.2A | 12-14.9Vdc | 13.33A | 160W |
| GT*961600P**** GT*961800P**** | | 15-18.9Vdc | 11.33A | 170W |
| GT*961600P**** GT*961800P**** | | 19-54Vdc | 9.47A | 180W |

Date: 17 September 2018

Signature: 